

RANGLER III

WING UP PACKER HARROW BAR

Model	36 feet		41 feet	
	Standard	Optional	Standard	Optional
1 3/4" (4.45 cm) Square Coil Packer, 130 lb./ft. (1.94 kg/cm) 19 3/4" (50 cm) Dia. 5 3/4" (14.6 cm) pitch with 2 Tapered Roller Bearing Sets.	X		X	
5-Bar Harrows with Straight Tine. 3/8" (0.95 cm) x 15" (38 cm) Long Tines.	X		X	
Dual Axle Main Frame - Tire Size - 11L x 15 FI - Load Range D	4		4	
Wing Axle Tire -7.60 x 15 - 6 ply rating	2		2	
Lift Cylinders - 4 1/2" (11.4 cm) Dia. x 30" (76.2 cm) Stroke	2		2	
Cart Frames - 2" (5 cm) x 6" (15 cm) Structural Tubing	X		X	
Wing Frames - 6" (15 cm) x 8" (20.3 cm) Structural Tubing	X		X	
Harrow Arms - 3" (7.6 cm) x 3" (7.6 cm) Angle		X		X
1 3/4" (4.45 cm) Square Coil Packer Kit (To pack behind the main frame tires). Used only with Packer Bar.		X		X
Safety Lights	X		X	
Safety Chain	X		X	
Standard Hitch - 133 7/8" (340 cm) Long	X		X	
Optional Hitch - 238 7/8" (607 cm) Long		X		X
Weight - With 1.5" Packers and 5 Bar Harrows	8,550 lbs. (3,886 kg)		9,310 lbs. (4,232 kg)	
Transport Height	14' 4" (4.37 m)		16' 9" (5.10 m)	
Transport Width	20' 3" (6.17 m)		20' 8" (6.30 m)	
Overall Length with Standard Hitch and Harrows	25' 5" (7.75 m)		25' 5" (7.75 m)	
60" (152 cm) Wide Harrows	6		3	
75" (190.5 cm) Wide Harrows	1		4	
31.75" (80.6 cm) Long Packer Coil	0		2	
43.75" (111 cm) Long Packer Coil	2		4	
54" (137 cm) Long Packer Coil	4		2	

Specifications are subject to change without notice.



MORRIS