

2200 BALE HIKER

LARGE ROUND BALE CARRIER

Length	42' (12.80 m)
Width Unloaded	Rails In - 9' 10" (3.00 m)
	Rails Out - 12' 8" (3.86 m)
Weight Unloaded	12,400 lbs. (5,625 kg)
Weight Loaded (GVWR)	46,000 lbs. (20,865 kg)
Load Capacity Weight	33,600 lbs. (15,241 kg)
Tires	(8) - 16L x 16.1FI - Load Range E 8 Bolt Hub
Transport Height	11' (3.36 m) minimum to 12' 4" (3.76 m) maximum
Automatic Bale Turner	Standard
Automatic Bale Unloading	Standard
Single Row Unloading	Optional
Frame - Tubing	Engineered Truss Design
Bale Divider - Adjustable	Standard - 12 positions
Side Rails - Adjustable	Standard
Cylinders - Fork - Bed Lift	1 - 4" x 18" (10.16 cm x 45.72 cm)
	2 - 4 1/2" x 18" (11.43 cm x 45.72 cm)
Selector Valve	Standard
Safety Lights	Standard
Safety Chain	Standard
Articulating Ball Hitch	1 1/2" or 2" (3.81 cm or 5.08 cm)
Tractor Requirement	180 HP (133 kW) Minimum (2 Remotes)
Bale Diameters	48, 60, 72 (1.22 m, 1.52 m, 1.83 m)

Individual Bale Weights

48" (1.22 m) Length	16 @ 2,100 lbs. (952 kg)
60" (1.52 m) Length	12 @ 2,800 lbs. (1,270 kg)